JAMECO®
ELECTRONIC COMPONENTS
COMPUTER PRODUCTS

1355 Shoreway Rd., Belmont, CA 94002
Tel: (415) 562-8097 Fax: (415) 592-2503 Domesctic Fax: (800) 237-6948
BBS: (415) 637-9025 Internet: http://www.jameco.com info@jameco.com
Order Toll Free (800) 831-4242

Part Number: 129525
Product Number: ADAM4520 (Isolated RS-232 to RS-422/485 Converter)

Input:	RS-232 (4 wire)
RS-232 Interface Connector:	Female DB9
Output:	RS-485 (2 wire) or RS-422 (4 wire) Speed: 1200, 2400, 4800, 9600, 19,2K, 38.4K, and RTS Control (switchable)
RS-422/485 Interface connector:	Plug-in screw terminal
Isolation Voltage:	$500V_{DC}$
Power Consumption:	1.2 W

*ADAM 4000 Series Common Specifications:

Communication

- RS-485 (2 wire) to host
- Speeds: 1200, 2400, 4800, 9600, 19200 bps
- Maximum communication distance: 4000 feet (1.2Km)
- Power and communication LED indicator
- ASCII command / response protocol
- Communication error checking with checksum
- Asynchronous data format: 1 start bit, 8 data bits, 1 stop bit, no parity
- Up to 256 multidrop modules per serial port
- On-line Module insertion and removal
- Transient suppression on RS-485 communication lines

Power Requirements

- Unregulated +10 to $+30V_{DC}$
- Protected against power reversal

Mechanical

- Case: ABS with captive mounting hardware
- Plug-in screw terminal block: accepts 0.5mm to 2.5mm 1 - #12 or 2 - #14 to #22 AWG

Environment

- Operating temperature: 14 to 158 degrees Fahrenheit (-10 to 70 degrees Celsius)
- EMI: Meets FCC class A
- Storage Temperature: -13 to 185 degrees Fahrenheit (-25 to 85 degrees Celsius)
- Humidity: 5 to 95%, non-condensing